

VMD-08

KEY FEATURES:

- 8 l/min of dry air
- Compact size
- Wall mountable
- Easy to use
- Powder coated Al. Cabinet

PRODUCT DESCRIPTION

The VMD-08 is a wall mountable Air dryer unit. It can supply up to 8l/min of dry air under normal conditions. The VMD-08 is used to supply a dry air source for units that use less than 8 l/min such as the HTU-500, POG, VMUS-2, and VMUS-4.



AZCO INDUSTRIES LIMITED
ADVANCED OZONE SYSTEMS



SPECIFICATIONS

	VMD-08	VMD-30	SNOA-1 (E*)
General			
Voltage [VAC, 50/60Hz]	100-120	100-120	100-120 (200-240)
Power Consumption [W]	Max 125	Max 250	Max 185
Ambient Temperature [°C]	2 to 40		
Relative Humidity [%]	92		
Mass [Kg]	3.0	7.2	6.3 (7.3)
Dimensions [L x W x H] [mm] <i>1 mm = .039 inches</i>	370 x 222 x 80	453 x 260 x 100	546 x 266 x 115
Installation	Refer to AZCO's installation manual for specific product		
Warranty [Refer to AZCO warranty sheet]	3 Year		
Ozone			
Generation Process	N/A	N/A	Pulse, Corona Discharge
Process Gas [bar] <i>1 bar = 14.5 psi</i>	Ambient air, free of dust and oil. Maximum pressure \pm 0.36		
Production on Oxygen [Refer to Graph for more detail]	N/A	N/A	~ 1 g/hr
Options			
Internal Air Pump	N/A	N/A	O (N/A)
Adjustable Output	N/A	N/A	O
Interlock	N/A	N/A	O
Flow Meter	N/A	N/A	O
Oxygen Ready	N/A	N/A	N/A
Vacuum Switch	N/A	N/A	N/A
Built-in Air Dryer	N/A	N/A	S
Safety			
CSA File #			
ETL File # [Canadian & US]			
UL File #			

E*: European Version, N/A: Not Applicable, O: Optional, S: Standard